



## IT3R10 REMOTE CONTROL RECEIVER

The receiver model IT3R10 is compatible with the whole range of radio remote controls Itowa.

Its new design is distinguished by its small dimensions, modularity and versatility.

Its design incorporates the latest technological advances together with other advantages such as the manipulation without tools, which reduces the costs of technical assistance and helps to intervene for programming and configuration.



# IT3R10

## Remote control Receiver


The IT3R10 receiver is designed for applications with a small number of commands. Its internal connector and cable gland output enables a quick connection of the manoeuvres, and the multi-option support offers great versatility in its installation.

It can incorporate the GCFI system (Intelligent Frequency Change Management) which allows detecting possible interferences in the working frequency and to be positioned in a new frequency so quickly that avoids the fall of the general contactor.

The receiver is compatible with all Itowa's radio remote control models.

### TECHNICAL SPECIFICATIONS IT3R10

Frequency bands	433-434 MHz 868-870 MHz
Sensibility	0,3μV
Nº of commands	10 (9+Start-Horn) + 2 Stop
Relays	Resistive charge: 5A to 250 Vac or 30Vdc
Power range	48Vac / 230Vac (-20% +15%) 24Vac / 24Vdc (-20% +15%) according to EN 60047-5-1
Display	Through 6 external led
Maximum consumption	0,1 A (48Vac) / 0,032 A (220Vac)
Connection	Internal connection through an Itowa connector of 26 pins and output by cable gland
Dimensions	(with support) 190 x 83 x 165 mm
Fuses	Emergency Stop operation 3A
Protection	IP65
Fixing	Fixing by bolts, Din rail, Magnetic as option
Weight	With magnetic fixing 0,890 Kgs
Security Level	Category 4 – SIL3/PL e in accordance to EN ISO 13849



Design and specifications subject to modifications without prior warning. 02/2021